

MVR-606-4IP

6CH Hybrid Mobile Digital Video Recorder

www.vipro.com.tw




Key Features

- 2CH WD1 + 4CH 720P IP in real time
- Rugged metal and modular design
- Excellent vibration performance
- 2.5" HDD storage and SD card mirror record
- Dual streams for local recording and wireless transmission
- GPS* for location tracking and Geo-fence
- 3G/4G* for live view and remote management
- WIFI automatic file download
- Power-off & surge protection, wide voltage input
- Durable in harsh temperature (-40°C~+70°C)

(*) Optional functions

Dimensions

(unit: mm)




Standard Accessories

Vehicle fuses (7.5A & 15A) x 2

MDVR key x 1



9 pin aviation power input wire x 1



Ultra-reliable HD hybrid performance coupled with everything you need for Mobile Video Security Management.

MVR-606-4IP is an advanced 6CH Hybrid Mobile Digital Video Recorder specially tailor-made for remote vehicle video surveillance solution. Incorporating embedded Linux O/S, high-speed processor and the latest H.264 video compression technology, MVR-606-2IP features built-in G-sensor, GPS positioning, Geo-fence alarm, 3G/4G cellular network connectivity, vehicle travel information recording and wireless data upload. With center software it also achieves alarm linkage central monitoring, remote management and playback analysis. Its modular and rugged design allows flexible installation and easy maintenance while ensures high reliability in harsh vehicle surveillance environment.

Technical Specifications

Product series		MVR-606-4IP
Overview		Preview, Record, Playback, Network, Locate
System	OS	Linux 3.0.8
	Control Mode	Mouse, Network, Easy Check, CP4
	Input	2 channels WD1 + 4 channels 720P
Video	Output	1 channel
	Total Resource	50/60fps @ WD1 + 120fps @ 720P
	Video Signal Standard	Electrical level: 1Vpp Impedance : 75Ω NTSC/PAL Optional
Audio	Input	6 channels (incl. IPC x 4)
	Output	1 channel
	Audio Signal Standard	Electrical level: 2Vpp Input impedance: 4.7kΩ
Display	Display Split	1/4/9
	OSD	GPS information, alarm, vehicle number, speed, date/time
	Operation	Semi-transparent GUI
Recording	Video/Audio Compression	Video: H.264 Audio:ADPCM, G.711A, G.711U
	Image Resolution	Analog: PAL:WD1(928x576),WHD1(928x288),WCIF(464x288), D1(704x576),HD1(704x288), CIF(352x288) NTSC:WD1(928x480),WHD1(928x240),WCIF(464x240), D1(704x480),HD1(704x240), CIF(352x240) Digital:720P(1280x720)
	Image Quality	1~8 levels adjustable (1 is the best)
Playback	Record Mode	Boot up/Manual/schedule/Alarm (sensor trigger, speed, acceleration, video loss, temperature)
	Pre-recording	0 ~ 60 minutes
	Post-recording	0 ~ 30 minutes
Network	Mirror/Dual Recording	Yes
	Playback Channel	1 channel by local playback
	Search Mode	Date/time, channel, event
Locating	Ethernet	RJ45 port (100M) x1
	IP Ethernet	6-pin DJ (100M x 2, PON power supply)
	WIFI	802.11b/g/n (optional)
Storage	3G/4G	EVDO/WCDMA/TDD-LTE/FDD-LTE (single module supported) (optional)
	GPS	location tracking, speed detection and sync time
	Hard Disk	2.5" SATA HDD x 1 (up to 2TB)
Interface	USB	USB 2.0 x 2 (1 for mirror record, 1 for easy check)
	SD	SD x 1
	RS232/RS485	RS232 x 2 / RS485 x 2
Electrical	Sensor	8 inputs, 2 outputs
	Serial	G-sensor (internal)
	Speed	1 channel pulse speed detection
Mechanical	Panel	CP4 (The multi-functional panel) optional
	Input	DC8~36V
	Output	12V@1A, 5V@1A
Environmental	Dimension	255.3 x 150 x 89.1mm / 10.05" x 5.906" x 3.508"
	Weight	2.2kg / 4.85lbs
	Operating Temperature	-40°C~+70°C / -40°F~+158°F (with heater)
Others	Temperature	-10°C~+70°C / -14°F~+158°F @ RH 8%~90%
	Waterproof	IP54
	PC Software	VMS 2.0
Certifications	EU / USA	CE, FCC

MVR-606-4IP

6CH Hybrid Mobile Digital Video Recorder

www.vipro.com.tw

Optional Accessories

GPS Module and Antenna

GPS data can be recorded into MDVR video files for playback and reported to CMS for real time vehicle positioning.



3G/4G Module and Antenna

Realize 3G/4G cellular network connectivity for Mobile DVR for live remote video streaming and alarm notification.



WIFI Module and Antenna

Multi-channel wireless network device applied for Mobile DVR on video download and data transfer.



4Pin Male-Female Din-jack Cable

Din-aviation cables are used for MDVR installation in the vehicle. 4 pins (video/audio/ground/power) can provide the power for cameras. Available in different lengths (1.5m,3m,5m,7m,9m,11m,13m,15m,20m or customized) to suit all kinds of vehicle installation.



Serial Connection Box

Integrate the interface of RS-232 and RS485 to realize the serial communication between external device and MDVR.



Serial Alarm Cable



6pin Aviation head to RJ45 Cable



6-Axis Sensor (G-force Sensor)

Determine a vehicle sharp turns, braking, intense bumps, rollover, fast changing lanes, S deformation tract and other bad driving habits by the detecting module and correct these bad behaviors via management system.



CP4 Control Panel

The multi-functional Control Panel used for Bus Dispatch System, featuring built-in amplifier, RFID, 7 inch LCD, station announcement.



LED Display Panel

Designed for easier checking of Mobile DVR working status. Any of the LED flash will indicate the corresponding status.



Easy Check

A device management software running on Android tablet, allowing user to manage the MDVR conveniently via the software in WIFI environment, thus improving working and maintenance efficiency.



HDD Reader

For playback recorded footage on PC



UPS (Uninterrupted Power Supply)

A high-performance back-up power solution, using internal electronic circuit to measure, calculate and storage battery data, which makes the use and management of power supply more predictable.



Fireproof Box

Specially designed for anti-fire and anti-explosion to protect the video files in the last minutes of the accidents with built-in 32GB memory.




MVR-606-4IP


6CH Hybrid Mobile Digital Video Recorder

www.vipro.com.tw

System Diagram




Front Panel



1. HDD module 2. Status LED 3. USB port

- PWR Power indicator lamp: Blue
- ALM Alarm indicator lamp: Red when alarm triggered, or light off.
- REC Record indicator lamp: Green when HDD or SD is recording.
- ERR Error indicator lamp: Red when hard disk works abnormally.
- NET Network indicator lamp: Green when there is 3G/4G module, otherwise, it is light off. It flashes when there is network.

Rear Panel



- | | |
|--------------------|--|
| 1. Power | DC 8-36 V Power Input |
| 2. Sensor & Serial | The Interfaces of Serial Port and Switch |
| 3. A/V IN 1~4 | Analog Audio & Video Input 1-4 |
| 4. IPC1~2 | PON Power Supply IP1~2 |
| 5. | GPS/BD Antenna Interface |
| 6. | 3G/4G Antenna Interface |
| 7. | WIFI Antenna Interface |
| 8. USB | USB 2.0 Interface |
| 9. LAN | Network Interface |
| 10. Panel | Control Panel Interface (CP4) |

SATA HDD Support List

Brand	Model	Capacity
Western Digital	WD5000LUCT	500G
	WD3200BUCT	320G
	WD10JUCT	1TB
	WD10SPCX	1TB
	WD3200LPVX	320G
	WD3200BPVT	320G
Toshiba	MQ01ABF032	320G
	MQ01ABF050	500G
	MQ01ABD100	1TB

*The above are recommended, but most SATA HDDs should work with 2TB max.

Brand	Model	Capacity
Samsung	ST1000LM024	1TB
	ST500LM012	500G
	ST320LM001	320G
	ST2000LM003	2TB
	HN-500MBB	500G
	HN-M101MBB	1TB
Samsung SSD	MZ-7WD480HCGM-00003	480G
	MZ7WD480HAGM-000H3	480G
Seagate	ST500LT012	500G
	ST500VT000	500G

MVR-606-4IP

6CH Hybrid Mobile Digital Video Recorder

Storage Capacity Calculation

① Image Quality and Stream

Resolution	Image quality	1	2	3	4	5	6	7	8
Stream (Kbps)	720P	6144	4800	4128	3456	2784	2112	1440	768
	WD1	2662	1997	1599	1331	1170	1040	936	832
	WHD1	1664	1248	998	832	728	650	585	520
	WCIF	1040	780	624	520	455	405	364	325
	D1	2048	1536	1230	1024	900	800	720	640
	HD1	1280	960	768	640	560	500	450	400
	CIF	800	600	480	400	350	312	280	250

② Record File Size Calculation

Each channel record file size:

Recording time (s) x Stream (Kbps) / 8 / 1024 = File Size (MB)

For instance, the file size of the image 1 at D1 resolution within 1 hour:

3600 x 2048 Kbps / 8 / 1024 = 900 MB

③ Image Quality and Resolution

Resolution	Image quality	1	2	3	4	5	6	7	8
Record (MB)	720P	2700	2109	1814	1518	1223	928	632	337
	WD1	1170	878	702	585	514	456	411	365
	WHD1	731	549	438	365	320	285	257	229
	WCIF	456	343	274	229	199	178	160	143
	D1	900	675	540	450	395	351	316	281
	HD1	562	422	337	281	246	219	198	176
	CIF	351	264	211	176	153	137	123	110