

EX-M82-IP Series

Explosion-proof IR Mobile IP Camera

www.vipro.com.tw



Key features

- Support RS485 serial port, extended with WIFI, 3G/4G function, built-in POE module, embedded web server, support IE browse video, parameter configuration, data update, user privilege management
- Support ONVIF protocol, open IP standard
- 5 million pixels 1/2.5" CMOS sensor, colour 0.6Lux@F1.2, Black and White 0.08Lux@F1.2
- Main stream: 1280x960, 1920x1080; Sub stream: 320x240, 352x192, 320x192, 288x192, 256x192
- Optics class toughened ultra-clear white explosion-proof glass, flux rate higher than 96%, completely eliminate infrared halos.
- IR night vision distance at 20-30m, high quality image showed even in badly lighting areas
- Optics class toughened ultra-clear white explosion-proof glass, flux rate higher than 96%, completely eliminate infrared light halos.
- Invisible nano wiper, non-stick water or oil
- 304 Electropolished stainless steel surface processing, elegant structure, explosion-proof, dust-proof, water-proof, rust-proof
- Intelligent 3D ring design, convenient to install at any angle, high quality pictures after adjustment

Ordered Model:

EX-M82-IP13M	IP 1.3Mega pixel
EX-M82-IP20M	IP 2.0Mega pixel

Accessory:

IR Bracket	Aluminum, wall mount, pole mount, used for proof shield & ex-proof cameras, load 30kg
Universal Joint	Aluminum, used for proof shield & ex-proof cameras, load 30kg
Ex-proof Flexible Tube BNG	Diameter: ϕ 15mm Length: 1200mm Interface: rubber $\frac{1}{2}$ ", $\frac{3}{4}$ " stainless steel $\frac{3}{4}$ " Temp: -25°C ~ +70°C
Ex-proof Junction Box	Interface: $\frac{1}{2}$ ", $\frac{3}{4}$ "
Ex-proof Control Box	Stainless steel

EX-M82-IP series is an explosion-proof IP Mobile Infrared Camera tailor-made for the rigorous requirements for hazardous areas. Featuring 304 stainless steel, simultaneous dual stream support and 3D ring design for various angle view, EX-M82-IP delivers the high image quality and reliability demanded in the most challenging environments.

Applicable for areas with the explosive mixtures formed from class IIA, IIB and IIC T1-T6 group flammable gas, steam with air in area No.1, No.2, and appearing the explosive hazardous area due to the mixture of flammable dust and air in area No.20, No.21 and No.22.

EX-M82-IP series is suitable for tanker, dangerous good transport vehicles, small warehouses, chemical reagents labs, pharmaceutical plants, explosion-proof elevator and also high requirements on size and weight places.

Technical Specifications

Product series		EX-proof IR Mobile IP Camera	
Model		EX-M82-IP13M	EX-M82-IP20M
Mechanical features	Material quality	304 Stainless steel	
	Surface treatment	Original stainless steel or Electro-polished surface (optional)	
	Anti-hazard classification	ExdIICT6 Gb / DIP A20 TA,T6	
	Ingress Protection	IP66	
	Interface spec	G-1/2"	
	Weight	≤4.0kg (8.818lbs)	
	Method of installation	Ceiling type & wall mounting	
	Dimension (L x D x H)	120x100x130(mm)/ 4.72"x3.93"x5.12"	
Camera	Resolution	960P	1080P
	Image Sensor	5 million pixels 1/2.5" CMOS sensor	
	Video Stream	Main: 1280x960	Main: 1920x1080
		Sub streams: 320x240, 352x192, 320x192, 288x192, 256x192	
	Video Processing	H.264 video encoding, support dual stream, AVI format, 0.1M~6Mbps adjustable	
	Frame Rate	25fps, 1~25 fps adjustable	
	Signal-to-Noise Ratio	>52dB	
	Minimum Illumination	Colour 0.6Lux@F1.2 B&W 0.08Lux@F1.2 (infra-red on)	
IR	Lens	4mm/6mm/8mm/12mm for option	
	IR Distance	20-30 meters	
Electrical	Wavelength	850nm	
	Input voltage	DC 12V	
	Working current	≤1A	
Environment	Electrical Connectivity	composite cable	
	Working temperature	-30°C~+70°C / -22°F~158°F	
	Atmospheric Pressure	86~106kpa	
	Relative Humidity	≤ 95%RH (±25°C)	
Certification		ATEX, CE, FCC	