



RS232/485 Connection Box integrate the interface of RS-232, RS-485 and so on, to realize the serial communication between the external device and Mobile Digital Video Record (MVR300 series).



Key Features

- Two RS-232 interfaces, to connect the automobile station reporter or the other external devices, etc.
- Two RS-485 interfaces, can be use to connect the PTZ or the other external devices, etc.
- Simple wiring
- Overall aesthetic
- Easy maintenance

Technical Specifications

Product series	RS232/485 wiring box
Series Interface	Two RS-232, Two RS- 485
Power Output	12/2A, 5V/1A
Working Temperature	-30°C~70°C
Storage Temperature	-40°C~85°C
Relative Humidity	≥95%
Cable Length	1000mm
Weight	225g
Dimension	69mm*71mm*21mm
Applied models	MVR 300 series

Dimension and Definition



- | | |
|--------------------------------|---------------------------------|
| 1. GND | 9. GND |
| 2. Connect peripherals 232 TXD | 10. Connect peripherals 232 TXD |
| 3. Connect peripherals 232 RXD | 11. Connect peripherals 232 RXD |
| 4. DC +12V | 12. DC +12V |
| 5. DC +5V | 13. DC +5V |
| 6. Connect peripherals 485A | 14. Connect peripherals 485B |
| 7. Connect peripherals 485B | 15. Connect peripherals 485A |
| 8. GND | 16. GND |