



ViPRO MVRs adopt the din-aviation connector, supporting 4 pins including video, audio, ground and power, which symbolizes that the Mobile DVRs can provide the power for the cameras. Din-aviation connector is the professional one for security products especially under the strong vibration condition. In certain content, this connector is waterproof and the connection is very strong to avoid the loose after long time usage and vibration.

If customers have no din-aviation connector for cameras, ViPRO can provide these transfer cables to customers as well. One end is din-aviation for Mobile DVR connection and another is BNC for camera connector.

Key Features

- Professional din-aviation connector for security products
- 4 pins (video/audio/ground/power) can provide the power for cameras
- The shielding cable which can avoid the external signal interference
- To transfer the din-aviation signal to be BNC if the cameras for Mobile DVR is BNC connector

Technical Specifications

Product series	Transfer Cable	
Connector	One end: Din-aviation	Another end: BNC (Video and Audio)
Connector Material	Din-aviation: Male connector: metal Female connector: Metal and plastic BNC: metal (with injection)	
Cable	Din-aviation part: 200mm: Din-aviation cable (4pins) BNC part: 100mm: standard the video and audio cable	
Cable Length	Total 300mm	
Voltage Input	+12 input	
Cable Diameter	Din-aviation: 6.5mm	standard A/V cable: 4mm

Dimensions and Pin Definition

